


Total Resin Extract

❖ Overview

- Total Resin Extract (TRE) is produced from aroma or bitter hop varieties through extraction with pure alcohol derived from fermentation. TRE contains all of the hop bitter acids (hard and soft resins) and hop oil components of the original leaf hops.
- TRE is added to the kettle and can be used to partially or entirely replace leaf hops, hop pellets or CO₂ hop extract.
- TRE offers a concentrated and practical alternative to leaf hops or hop pellets with an identical bitter. Moreover, TRE has a long shelf life.

Composition of hop resin in leaf hops and TRE



❖ Specifications

Description: dark green extract, highly viscous at room temperature

Steiner Hops Ltd.

Epping, England

Tel: (44) 1992 572331

Fax: (44) 1992 573780

E-mail: enquiries@hopsteiner.co.uk

Alpha acids*: 20 – 55 %
Beta acids*: 15 – 30 %
Iso-alpha acids: 0.5 – 2.0 %

• Hop oil*: approx. 3 – 12 %

Residual ethanol: < 0.3 %
pH: 6.2 (± 0.5)

Viscosity: 400 – 1000 mPas at 45 °C (113 °F)
Density: approx. 1.0 g/ml at 20 °C (68 °F)

*dependent on variety and crop year



Properties

Appearance

Dark green in color, TRE is a thick syrup/paste that becomes more fluid when warmed.

Utilization

If TRE is boiled for at least 50 minutes, utilization in the range of 30 - 40 % can be expected. Actual utilization will vary from brewery to brewery due to differences in equipment and process conditions.

Flavor

The flavor especially bitter and the characteristics of the original hops are completely retained. Early additions of TRE during wort boiling mainly serve to impart bitterness.

Chemical Residues

Nitrates and heavy metals are significantly lower in **TRE**. In addition, pesticide residues removed the largely by are ethanol extraction process.

Quality

All Hopsteiner® products are processed in facilities which fulfill internationally recognized quality standards.

❖ Packaging

TRE can be packaged in cans and drums according to customer requirements:

Cans: 0.5 to 4.2 kg Drums: 50 and 200 kg TRE can be produced to any alpha acid concentration desired by our customers and packaged in cans (e.g. 450 g of alpha acids per can).

Alternatively, the alpha acid content of TRE be standardized to any given concentration using glucose syrup The container is then filled to a standard weight (e.g. 30 % alpha acids in 1 kg cans).

❖ Product Use

TRE is typically added to the wort kettle as a complete or partial replacement for leaf hops or hop pellets.

Dosage

Kettle additions of TRE are based on the concentration of bitter substances (CBV), an estimated or known utilization and the desired intensity of bitterness in the beer.

Application

For the highest possible utilization, TRE should be added early in the wort boiling process. TRE is not very suitable for late hop additions due to its nonpolar character. However, in this situation, better results can be achieved with pre-isomerized kettle extracts such as IKE or PIKE, products that are more soluble in wort.

Pre-warming cans of TRE is not necessary. Suspending punctured cans in the boiling wort will ensure that all of the extract is completely flushed out into the kettle.

Simon H. Steiner, Hopfen, GmbH

S.S.Steiner, Inc.

New York, USA



If **TRE** is added by means of automatic dosing units, it should be warmed to 45 °C (113 °F) and gently mixed to ensure perfect dosing.

Storage

TRE should be stored in sealed containers at temperatures < 10 °C (50 °F). Opened containers should be used within a few days.

Best Before Date

TRE is stable for eight years from the date it was produced / packaged if stored under the recommended conditions.

Safety

TRE is a natural substance and may be safely handled using routine precautions to avoid contact with skin and, in particular, the eyes. Any product coming into contact with the skin should be washed off immediately with soap and water or an appropriate hand cleanser. If TRE gets into the eyes, flush with copious amounts of water until clear and seek medical attention.

For full safety information, please refer to the relevant Hopsteiner® safety data sheet.

❖ Analytical Methods

Concentration of Bitter Substances

Iso-alpha, alpha and beta acids can be measured with the current standards using the following methods:

- HPLC according to Analytica-EBC 7.8
- ASBC Hops-16

The lead conductance value can be measured using the following methods:

- Analytica-EBC 7.6
- ASBC Hops-8 (II)

TRE is normally dosed according to its <u>Conductometric Bitter Value</u> (CBV) as this value better represents its bitterness potential.

Note: CBV = LCV (EBC 7.6) + 50 % of isoalpha acids (EBC 7.8)

Concentration of Hop Oil

The hop oil concentration can be measured using the following methods:

- Analytica-EBC 7.10
- ASBC Hops-13

❖ Technical Support

We are pleased to offer assistance and advice on the full range of Hopsteiner® products:

- o copies of all relevant analytical procedures
- Safety Data Sheets (SDS)
- assistance with pilot or full-scale brewing trials
- special analytical services

Disclaimer: The information provided in this document is believed to be correct and valid. However, Hopsteiner® does not guarantee that the information provided here is complete or accurate and thus assumes no liability for any consequences resulting from its application.

Steiner Hops Ltd.